

D43-XXX300/450R

Door type: door panel width mm (X_{total}), max opening mm

D43-XXX300R: 500 - 3000 mm, 405,5 - 2905,5 mm

D43-XXX450R: 750 - 4500 mm, 634,5 - 4385,5 mm

XXX= Height on posts



Total width of door (300R) = 4560 mm = Y + X1 + X2 + 160

Total width of door (450R) = 6160 mm = Y + X1 + X2 + X3 + 160



Max opening (300R) = X (panel width) - 94,5 mm (94,5 mm = 40 + 20 (panels overlapping) + 34,5)
Max opening (450R) = X (panel width) - 114,5 mm (115,5 mm = 40 + 40 (panels overlapping) + 34,5)
(P) Post to post opening (300R) = X (panel width) - 60 mm** (**= panel in closed position overlapping posts (60 mm = 40 + 20))
(P) Post to post opening (450R) = X (panel width) - 80 mm** (**= panel in closed position overlapping posts (80 mm = 40 + 40))
50# and 20# = Dimensions in door closed position
Max opening is affected by "A" mm with lock (without door accessories*)

Item No.	Art No.	Qty.	
		300R	450R
X (1,2..)	322-XXXXXX	2	3
Y	W322-XXXXXX	1	1
Z	P13-XXX	3	3

Locks	A (lock to X1 (300R) / X2 (450R))
L20-05-0 (Snap lock)	-
L20-05-2 (Hitch lock)	105 mm
XIT-L/R01-301 (Cylinder lock)	-
XIT-L/R14-301 (Slam shut)	215 mm
XIT-L/R09-301 (Electric)	-
L66-20/21-L/R (X-lock)	190 mm
B-135 (MGB)	-
B-136 (MGB Escape Release)	135 mm